

MITEL NETWORKS

5207 | IP Phone**Affordable Multi-line
IP Speakerphone**

The Mitel Networks™ 5207 IP Phone is an entry-level multi-line, user-programmable IP speakerphone with an easy-to-read backlit display. It is designed primarily for users requiring multiple line appearances and feature keys.

Multiple-line Access

The 5207 IP Phone is specifically designed as a cost-effective choice for any user or location in your operation that requires multiple-line access to advanced telephony features and user applications. Features include multiple programmable keys and an easy-to-read backlit orange LCD display.

Industry's Widest Range of IP Phones

The 5207 IP Phone is one in a series of IP phones designed to meet the diverse communication needs of users across the enterprise – from affordable entry-level IP phones to sophisticated network appliances. All are designed with ergonomics and modern office esthetics in mind.

Features

- Hands-free speakerphone operation (half duplex)
- Single port, multiple lines
- 20-character backlit display with contrast control
- 14 programmable multi-function keys with dual-color LED indicators (for speed dialing, line appearances, feature keys)
- 8 fixed function keys: Hold, Superkey/Program, Transfer/Conference, Cancel, Speaker, Microphone, Message, Redial
- Dual-color LEDs
- Call hold (I hold, You hold)
- Speed dialing
- On-hook dialing
- Voice mail access – large message waiting lamp
- Call forward
- Group page
- Distinctive ringing
- Intercom calling
- Handsfree answerback
- Phonebook directory access
- Call park and paging
- Calling line identification
- Customizable center panel
- Wall mountable

it's about **YOU**

Voice QoS

Supports 802.1p/q for quality of service.

Powering Options

Available with Ethernet AC adapter; accepts standards-based (IEEE 802.3 af) power over the LAN via spare or signal pair.

Environmental Conditions

	Temperature	Humidity
Operational	+4°C - +40°C	34%
Storage	-25°C - +66°C	15%

Regulatory Standards

EMC CLASS B (FCC-Part 15)
Network FCC-Part 68 (US), CS-03 (Canada)

System Requirements

- Mitel Networks SX-200 Integrated Communications Platform, release 1.0

5207 IP Phone Specifications

Ports	AC Adapter	Consumption	Processor Type	Processor Speed	Silicon	Package
1	Output: 48 Vdc 250 mA Input: 110 V 50-60 Hz 220 V 50 Hz	2 W	ARM7TDMI	25 MHz	0.18µ CMOS	QFP
Voice Traffic	Signaling	Ethernet	Size (LxW)	Weight	MTBF Rate	Compression
RTP over UDP	MinET over TCP	IEEE 802.1p/q	7" x 9.25" 17.8 cm x 23.5 cm	2.8 lbs 1.3 kg	10 yrs	G.711

North America	Europe, Middle-East & Africa	Latin America	Asia-Pacific
(613) 592 2122 1 800 648 3579	Sales: 0870 9093030 Int: +44 (0) 1291 430 000	(613) 592 2122 1 800 648 3579	Tel: +852 2508 9780 Fax: +852 2508 9232

www.mitel.com



THIS DOCUMENT IS PROVIDED TO YOU FOR INFORMATIONAL PURPOSES ONLY. The information furnished in this document, believed by Mitel Networks to be accurate as of the date of its publication, is subject to change without notice. Mitel Networks assumes no responsibility for any errors or omissions in this document and shall have no obligation to you as a result of having made this document available to you or based upon the information it contains.

M MITEL (design) is a registered trademark of Mitel Networks Corporation. All other products and services are the registered trademarks of their respective holders.

© Copyright 2003, Mitel Networks Corporation. All Rights Reserved.

GD 6732 PN 51006870, Rev. A