



A MITEL
PRODUCT
GUIDE

Mitel InAttend

InAttend and CMG Solution Engineering Guide

Release 2.6 SP4

BOOK PART NUMBER: 29/1531-ANF 901 89 Uen

October 2022

Notices

The information contained in this document is believed to be accurate in all respects but is not warranted by **Mitel Networks™ Corporation (MITEL®)**. The information is subject to change without notice and should not be construed in any way as a commitment by Mitel or any of its affiliates or subsidiaries. Mitel and its affiliates and subsidiaries assume no responsibility for any errors or omissions in this document. Revisions of this document or new editions of it may be issued to incorporate such changes. No part of this document can be reproduced or transmitted in any form or by any means - electronic or mechanical - for any purpose without written permission from Mitel Networks Corporation.

Trademarks

The trademarks, service marks, logos and graphics (collectively "Trademarks") appearing on Mitel's Internet sites or in its publications are registered and unregistered trademarks of Mitel Networks Corporation (MNC) or its subsidiaries (collectively "Mitel") or others. Use of the Trademarks is prohibited without the express consent from Mitel. Please contact our legal department at legal@mitel.com for additional information. For a list of the worldwide Mitel Networks Corporation registered trademarks, please refer to the website: <http://www.mitel.com/trademarks>.

®, ™ Trademark of Mitel Networks Corporation

© Copyright 2022, Mitel Networks Corporation

All rights reserved

Contents

1 Introduction.....	1
2 Server dimensioning.....	2
2.1 System with InAttend and CMG server.....	2
2.1.1 Notes.....	4
2.1.2 SQL Server editions.....	5
2.1.3 Presence Capacity Testing.....	5
2.2 System with InAttend Standalone.....	6
2.3 InConference.....	8
2.4 Media server.....	8
2.5 Web server.....	9
2.6 Disk space.....	10
2.6.1 Nuance language packages.....	10
2.6.2 Log files.....	10
2.6.3 Voice mail and recordings.....	11
2.7 Network bandwidth (InAttend client).....	11
2.8 Complex environments.....	12
2.9 InAttend and CMG Server on the Azure Environment.....	12
3 Redundancy.....	13
4 Virtualization.....	14
5 Technical Assistance.....	15
6 References.....	16

InAttend is a powerful, user-friendly attendant application designed for handling high volumes of internal and external calls in an efficient way. Call and activity handling, presence and availability with line status information are all integrated into one single application.

The Attendant Connectivity Server (ACS) is the Telephony server providing the telephony functionalities over IP. The InAttend client works in combination with ACS to provide an advanced attendant platform for the supported SIP enabled call managers. See InAttend Compatibility Matrix [3] for a list of the supported call managers.

i Note:

The Compatibility Matrix document is available on InfoChannel.

This document describes the engineering guidelines for the Mitel InAttend solution, including Contact Management (CMG) and Virtual Reception.

This chapter contains the following sections:

- [System with InAttend and CMG server](#)
- [System with InAttend Standalone](#)
- [InConference](#)
- [Media server](#)
- [Web server](#)
- [Disk space](#)
- [Network bandwidth \(InAttend client\)](#)
- [Complex environments](#)
- [InAttend and CMG Server on the Azure Environment](#)

The information in this section is intended as a guideline for dimensioning a typical solution including Contact Management (CMG), InAttend and optionally, Calendar Connection and the Speech products.

2.1 System with InAttend and CMG server

The following table lists the recommended capacity limits for different server configurations. If any of the recommended capacity values must be exceeded, a more powerful server configuration must be used. These recommendations are made assuming a CPU core speed of 2.4GHz or greater for all configurations.

The guidelines also include a typical specification for heavy-load usage scenarios, which refers to how much load the system is expected to handle while keeping the CPU usage below 40%. It is recommended not to significantly exceed this usage limit. For usage for which this limit might be exceeded, a more powerful configuration is required. It is also assumed that an anti-virus software is installed on the system but configured with exceptions according to the product documentation.

The guidelines use the following groups of components to indicate how to distribute the software in multi-server deployments:

- **CMG:** Contact Management (CMG) Server, including CMG Web; can also include the Calendar Server, Speech main server, Visit, and Quality Manager.
- **SQL:** Microsoft SQL Server
- **ACS:** All Attendant Connectivity Server (ACS) components (Queue Manager, NeTS and Media server). Can also include Speech Telephony server components, InConference and Nuance.

CMG Visit and Quality Manager can be installed on the CMG Server without having to add additional hardware, as these components do not add any significant load on the server.

Table 1: System capacity and component distribution

Users	1 - 500	501 - 1000	1001 – 5000	> 5000
Capacity				
Concurrent attendants	Up to 4	Up to 6	Up to 20	> 20
Concurrent ASR channels	2	3	11	> 11
SQL Server Express supported 1	CMG: Yes BSS: Yes	CMG: Yes BSS: Yes	CMG: No BSS: Yes	CMG: No BSS: Yes
TYPICAL HIGH USAGE (PER MINUTE)				
Attendant calls	12	24	60	Please contact your Mitel sales representative for recommendations
CMG Web searches	15	30	90	
Speech Attendant calls	8	16	30	
Calls to listen to / record voice mail	3 / 6	6 / 12	12 / 32	
Hardware requirements				

System with CMG and InAttend	Server 1 CMG, SQL, BSS, ACS 4 CPU cores8 GB RAM	Server 1 CMG, SQL, BSS 4 CPU cores8 GB RAM Server 2 ACS 2 CPU cores4 GB RAM	Server 1 CMG, SQL 6 CPU cores8 GB RAM Server 2 ACS 4 CPU cores8 GB RAM Server 3 BSS, SQL2 2 CPU cores8 GB RAM	
Users >5000	1 - 500	501 - 1000	1001 - 5000	
Calendar Connection	(included)	(included)	(included)	
Speech Office	Add: 1 CPU core	(included)	Add to ACS:1 CPU core	
Speech Attendant	Add: 1 CPU core	Add to ACS:1 CPU core	Add to ACS:2 CPU core	

2.1.1 Notes

- CMG Server can use SQL Server Express, except when used in redundancy mode together with SQL Server Failover Clustering.
- If InAttend Server is running on the same server as CMG, InAttend Server uses the same SQL Server as CMG. If CMG Server is running on a separate server, CMG Server should have a local SQL Server.

2.1.2 SQL Server editions

Microsoft SQL Server is used by multiple components within the InAttend and CMG solution. The solution supports both Microsoft SQL Server Express (for some configurations) and all the full editions of Microsoft SQL Server. The SQL Server Express edition is limited to use up to 4 CPU cores, 1 GB RAM and 10 GB database size, and is for that reason not supported for all components and system sizes.

For CMG (including CMG Speech and all components except CMG Server), SQL Server Express is only supported for installations up to 1000 users. Above 1000 users, SQL Server Standard edition or above is required.

Please refer to the Compatibility Matrix for a complete list of supported versions of Microsoft SQL Server.

2.1.3 Presence Capacity Testing

With Live Presence enabled in CMG Web -> Parameters of CMG CM, below is the limitation which is recommended.

Capacity	
Users	500/5000 (monitored)
Concurrent IA clients	20
Concurrent CMG Web Clients	20

Subscription Burst	Searches	Linestate (IA)	Linestate (CMG Web)
200	25	Stable	Stable
	50	Stable	Stable
	100	Stable	Stable

Note:

For heavy CMG web client usage, it is recommended to turn off live presence in CMG Web->Parameters of CMGCM.

2.2 System with InAttend Standalone

The following table lists the recommended capacity limits for different server configurations. If any of the recommended capacity values must be exceeded, a more powerful server configuration must be used. These recommendations are made assuming a CPU core speed of 2.4GHz or greater for all configurations.

The guidelines also include a typical specification for heavy-load usage scenarios, which refers to how much load the system is expected to handle while keeping the CPU usage below 40%. It is recommended not to significantly exceed this usage limit. For usage for which this limit might be exceeded, a more powerful configuration is required. It is also assumed that an anti-virus software is installed on the system but configured with exceptions according to the product documentation.

The guidelines have considered the following groups of components in indicating how to distribute the software in multi-server deployments:

AD server

SQL: Microsoft SQL Server


ACS: All Attendant Connectivity Server (ACS) components (Queue Manager, NeTS and Media server).

Table 2: System capacity and component distribution

Users	1 - 500	501 - 1000	1001 – 5000	> 5000
Capacity				
Concurrent attendants	Up to 4	Up to 6	Up to 20	> 20
TYPICAL HIGH USAGE (PER MINUTE)				
Attendant calls	12	24	60	Contact your Mitel sales representative for recommendations
Hardware requirements				

Standalone Server	4 CPU cores, 6 GB RAM	4 CPU cores, 8 GB RAM	4 CPU cores, 8 GB RAM	Contact your Mitel sales representative for recommendations
-------------------	-----------------------	-----------------------	-----------------------	---

Client requirements:

Processor	1 gigahertz (GHz) or faster compatible processor or System on a Chip (SoC). Refer <i>Microsoft recommendation</i>
RAM	6 GB RAM or higher
Hard drive size	32GB or larger hard disk
	<div>  Note: See Microsoft recommendation on <i>hard drive space to install or update Windows 10</i> for more details. </div>
Recommended OS	Windows 10

Server Requirements

Processor	2.4 gigahertz (GHz) or faster (Refer <i>Microsoft recommendation</i> for supported OS), 4 CPU Cores
RAM	8 GB RAM or higher
Hard drive size	64 GB or larger hard disk

Recommended OS	Windows 2019 Server, Windows 2016 Server
-----------------------	--

2.3 InConference

InConference is not included in the server dimensioning guidelines described in the previous section because the dimensioning depends on how many users use the conferencing feature.

The table below gives recommendations for how many additional CPU cores that must be added to the server running the Media server when InConference is used, assuming the G.711 codec is used. The conference participants is the total number of all conference participants across all ongoing conferences.

Additional hardware resources for InConference

Conference participants	Additional CPU cores on Media server
Up to 20	No additional CPU cores required
21 – 100	1 additional CPU core required
101 – 200	2 additional CPU cores required
201 – 400	4 additional CPU cores required
> 400	Please contact your Mitel sales representative for recommendations

2.4 Media server

For small and medium size systems, the media server is installed with the other ACS components as indicated in the main dimensioning table. For very large systems, the media server can be installed on multiple servers for load balancing.

The table below lists the features in the InAttend and CMG Speech solution that requires media sessions.

Feature	Required number of media sessions
Attendant in call	2 sessions per attendant
Calls in queue	1 session per call
Speech Attendant	2 sessions per concurrent user
Speech IVR	1 session per concurrent user
InConference	1 session per conference participant

The table below lists the number of concurrent media sessions the Media server can handle depending on the codec being used. The number of sessions are stated with a significant margin to be able to handle short peaks in usage.

Codec	Media sessions per CPU core
G.711 / G.722	100 sessions per CPU core
G.729	70 sessions per CPU core

2.5 Web server

Web applications (e.g., CMG Web), can be deployed on a different web server, separate from the CMG server. For example, CMG Web can be deployed on a web server in the Demilitarized Zone (DMZ) to allow access from the Internet.

The web server should meet the hardware requirements for an IIS server provided by Microsoft. The following table summarizes the dimensioning guidelines for CMG Web running on a separate web server.

Web server hardware requirements

Hardware component	Requirements
CPU	<p>50% of the number of CPU cores required by the CMG Server if the usage is within the typical usage range (see main dimensioning table).</p> <p>Same number of CPU cores required by the CMG Server if the usage is significantly higher than typical usage.</p>
Memory	Same as the CMG Server.

2.6 Disk space

The software footprint is small compared to a complete server installation with Windows Server and SQL Server installed. However, the recommendation is to have at least 30 GB of free disk space before the software is installed. In addition, there must be disk space available for Nuance language packages (if used), log files, voice mail and recordings.

2.6.1 Nuance language packages

When using CMG Speech with Nuance, each language requires a Nuance language package. See the table below for the request disk space for each language package.

Nuance	Required disk space per language
TTS language	Up to 1 GB
ARS language	Up to 0.5 GB

2.6.2 Log files

It is recommended to reserve at least 60 GB of disk space for log files on each server.

2.6.3 Voice mail and recordings

Voice mail messages and recordings in InAttend or InConference are stored as .wav files on the disk. The size of the wave files depends on the quality setting, as summarized below:

Quality setting	Required disk space
8 bit, 8 KHz (default)	29 MB per hour
16 bit, 16 KHz	115 MB per hour

2.7 Network bandwidth (InAttend client)

The InAttend softphone requires 100 kbit/s when the attendant is in a call. When using hardphone, this bandwidth will not be used by the InAttend client. InAttend also requires at least 100 kbit/s for operations like searching, reading call log and all other features in the client. This bandwidth is not used all the time, only when performing the operations.

InAttend will also require 20 kbit/s (per client) for each 1000 calls per hour that the system is receiving. For example, a system with 2000 calls per hour will require 40 kbit/s for the call traffic. This bandwidth is required to perform directory lookup of queue entries and adding entries to the call log.

Client feature	Required bandwidth per InAttend client
Softphone	100 kbit/s
Operations	100 kbit/s
Traffic	20 kbit/s per 1000 calls/h

2.8 Complex environments

For dimensioning of very large installations or installations with high, please contact your Mitel sales representative for assistance.

2.9 InAttend and CMG Server on the Azure Environment

The following table lists the recommended capacity limits for Azure Environment.

The guidelines also include a typical specification for heavy-load usage scenarios, which refers to how much load the system is expected to handle while keeping the CPU usage below 40%. It is recommended not to significantly exceed this usage limit.

Table 2.3 : System Capacity

Users	5000
Capacity	
TYPICAL HIGH USAGE (PER MINUTE)	
Concurrent Attendants	20
Attendant Calls	60
CMG Web searches	90
Hardware Requirements	
System with CMG and InAttend	Standard D2s v3 (2 vCPUs and 8GiB memory)

The InAttend and CMG solution supports two redundancy solutions; Hot-standby servers and VMware High Availability. In both these cases, the redundant servers must be dimensioned in the same way as the primary servers.

The InAttend solution supports virtualization using VMware. The system requirements for virtual environments are identical to the requirements for environments where the software runs on physical servers.

If the solution is deployed in a virtual environment, enough resources must be dedicated for the virtual servers, as the software requires real-time processing of calls and media. This requirement is especially important when running media servers in a virtualized environment.

If it is not possible to dedicate enough resources to the virtual servers running the media server, the media server can be installed on a physical server outside the virtual environment.

Please refer to the Compatibility Matrix for a list of supported virtual environments.

Mitel provides www.mitel.com as a starting point for technical assistance regarding all products, including the CMG application suite. From here, partners can obtain online documentation, FAQs, latest software updates and request further technical assistance.

[1] InAttend System Overview

[2] InAttend Installation and Configuration Guide

[3] InAttend Compatibility Matrix (Note: Available on InfoChannel)

[4] InAttend Redundancy

