

# Free seating

OPERATIONAL DIRECTIONS



## NOTICE

The information contained in this document is believed to be accurate in all respects but is not warranted by Mitel Networks™ Corporation (MITEL®). Mitel makes no warranty of any kind with regards to this material, including, but not limited to, the implied warranties of merchantability and fitness for a particular purpose. The information is subject to change without notice and should not be construed in any way as a commitment by Mitel or any of its affiliates or subsidiaries. Mitel and its affiliates and subsidiaries assume no responsibility for any errors or omissions in this document. Revisions of this document or new editions of it may be issued to incorporate such changes.

No part of this document can be reproduced or transmitted in any form or by any means - electronic or mechanical - for any purpose without written permission from Mitel Networks Corporation.

## TRADEMARKS

The trademarks, service marks, logos and graphics (collectively "Trademarks") appearing on Mitel's Internet sites or in its publications are registered and unregistered trademarks of Mitel Networks Corporation (MNC) or its subsidiaries (collectively "Mitel") or others. Use of the Trademarks is prohibited without the express consent from Mitel. Please contact our legal department at [legal@mitel.com](mailto:legal@mitel.com) for additional information. For a list of the worldwide Mitel Networks Corporation registered trademarks, please refer to the website: <http://www.mitel.com/trademarks>.

© Copyright 2017, Mitel Networks Corporation

All rights reserved

# 1 GENERAL

## 1.1 INTRODUCTION

The purpose of the feature Free seating is to provide the user the possibility to move between (log on to) different physical telephones and still keep the categories of the free seating (the own) number.

## 1.2 GLOSSARY

For a complete list of abbreviations and glossary, see the description for *ACRONYMS, ABBREVIATIONS AND GLOSSARY*.

# 2 PREREQUISITES

The generic extension directory numbers, and directory number related data must be initiated, see the command description for *extension*.

Category CSP must have --ext-serv D18 set to 1 to enable service free seating.

The free seating function also requires that an individual authorization code (RAC) is initiated in the system, see the command description for *Authorization code*.

# 3 TOOLS

I/O terminal.

# 4 REFERENCES

In these operational directions references are made to the following documents:

<b>Command Descriptions:</b>	<i>auth_code</i> <i>EXCCS</i> <i>extension_profile</i> <i>extension</i> <i>KSEXl</i> <i>name</i> <i>number_initiate, number_end</i> all in the <i>Technical Reference Guide, unix commands</i>
<b>Operational Directions:</b>	-

## 5

## PROCEDURE

To be able to use the feature free seating in the system the feature has to be initiated in 2 steps. The generic extension must be initiated and the individual authorization code. If wanted, name identity can also be used.

### **Initiation:**

- Initiate a directory number in the extension number series.
- Initiate the directory number as a generic extension.
- Initiate an individual authorization code for the generic extension.
- Initiate name identity, if wanted, for the generic extension.

### **Removal:**

- Remove name identity, if used, for the generic extension.
- Remove the individual authorization code for the generic extension.
- Remove the generic extension.
- Remove the directory number in the extension number series.

## 6

## EXECUTION

### Initiation:

- Key the command *number\_initiate* to initiate directory numbers.
- Key the command *extension\_profile -i* and *extension -i* to initiate common service profiles and generic extensions.
- Key the command *auth\_code* to initiate individual authorization codes.
- Key the command *name -i* to initiate name identity.

### Removal:

- Key the command *name -e* to remove name identity.
- Key the command *auth\_code* to remove individual authorization codes.
- Key the command *extension -e* and *extension\_profile -e* to remove generic extensions and common service profiles.
- Key the command *number\_end* to remove directory numbers.

## 7 EXAMPLE

### 7.1 GENERAL

This example shows the steps to initiate a free seating extension. When the free seating extension is initiated successfully, the free seating log-on and log-off procedure can be executed from the DTS. Generic extensions instead use the ordinary login procedure.

### 7.2 PREREQUISITES

- Free Seating Number: 11111
- DTS Number: 21000
- PIN Number: 1234

### 7.3 EXECUTION

#### Initiation of generic extension categories

```
extension_profile -i --csp 1 --ext-traf 1103151515 --ext-serv
2121321100010000010000000000 --ext-cdiv 11100000000000 --ext-roc 000001
--ext-npres 0001000
```

#### Initiation of number series for Free Seating extension

```
number_initiate -numbertype ex -number 11111
```

#### Initiation of Free Seating extension

```
extension -i --dir 11111 --csp 1 --lim 1 --virtual yes
```

**Note:** License for virtual extension must be available.

#### Initiation of name identity for Free Seating extension

```
name -i --dir 11111 --name1 "DAVID" --name2 "ARKENSTONE" \ --number-type dir
```

#### Initiation of individual authorization code

```
auth_code -i -d 11111 --csp 1 --cil 111111 --customer 0 --auth-code 1234
```

#### Initiation of non-generic extension categories

```
EXCCS:CAT=12,TRAF=03151515,SERV=02021200000000,CDIV=00015111100,
ROC=000001;
```

#### Initiation of number series for DTS extensions

```
number_initiate -numbertype ex -number 21000
```

#### Initiation of digital extensions

```
KSEXI:DIR=21000,EQU=2-0-50-0,CAT=12,ITYPE=20,ADC=00001113010000;
```

## 8

## TERMINATION

If free seating numbers have been added or removed, inform the department (person) responsible for directory information.

A dump to backup media shall be performed if any configuration data have been altered.